

LPH-SMA-R-A35-0

Laser Process Head for advanced Material Processing



product similar to image

| Laser Material Processing |

Your product benefits:



- Optimized beam shaping for your application
- Low residual divergence

Laser Process Head	Unit	Value		Unit	Value
Optical Data			Mechanical Data		
Max. laser power (cw)	W	120	Housing material		anodized aluminum
Wavelength range	nm	790 - 990	Dimensions (height x width x depth)	mm	70 x 70 x 72
Max. numerical aperture of fibre		0,23	Mounting threads		4 x M5
Max. fiber core diameter	µm	600	Fiber connector types		SMA905
Transmission rate		≥ 90% (typ. 95 %)	Thermal Operation and Storage Conditions		
Collimation focal length	mm	35	Operation ambient temperture range	°C	5...40
Focussing focal length	mm	na	Max. operation relative humidity		non condensing
Working distance	mm	na	Storage temperature range	°C	20...50
Max. divergence with 200 µm fibre *	mrad	6	Storage max. relative humidity		non condensing
Max. divergence with 400 µm fibre *	mrad	12	Max. housing temperature in operation	°C	60
* FW 1/e ²					

Additional Features	Unit	Value		Unit	Value
Pyrometer Control Data			Power Monitoring Data		
Detection wavelength	nm	not available	Wavelength range	nm	not available
Temperature measurement range	°C	not available	Sampling rate (standard)	kHz	not available
Sampling rate (standard)	kHz	not available	Operation temperature range	°C	not available
Calibration standard type		not available	Measurement accuracy	%	not available
Interface Data			Related Product		
Interface type		not available	Process software		not available
Data cable type		not available			
Socket type		not available			
Communication protocol of laser driver		not available			

LPH-SMA-R-A35-0

Laser Process Head for advanced Material Processing



LPH-SMA-R-A35-0

Copyright © 2012 LIMO GmbH. All rights reserved. All LIMO products are patent pending. Subject to change without notice.

Version May 18, 2015